

Silkolene®

SILKOLENE PRO 4 XP RANGE

Extreme performance, fully synthetic ester, 4-Stroke engine oils for all high performance motorcycles

Description

The SILKOLENE PRO 4 XP range of motorcycle engine oils are designed using XP Technology for high performance On-Road and Off-Road 4 stroke motorcycle engines. XP Technology uses an innovative highly shear stable, low volatility base oil formulation along with stable esters to achieve increased power, provide ultimate engine and transmission protection, reduce oil consumption and improve fuel economy even under race conditions. XP Technology combats engine wear and reduces friction on all critical load surfaces at both high temperature operation and on cold starts.

Application

The SILKOLENE PRO 4 XP range is formulated to meet the needs of both air and water-cooled 4-Stroke engines fitted to Road and Off-Road motorcycles. PRO 4 XP comes in three grades to provide the correct viscosity for the majority of motorcycle manufacturers.

SILKOLENE PRO 4 5W-40 XP
SILKOLENE PRO 4 10W-30 XP
SILKOLENE PRO 4 10W-40 XP
SILKOLENE PRO 4 15W-50 XP
SILKOLENE PRO 4 10W-50 XP
SILKOLENE PRO 4 10W-60 XP

Specifications / Approvals

- JASO MA2
- API SN Performance

Advantages

- One product range suitable for all high performance 4-stroke motorcycle engines On-Road and Off-Road
- Racing and dyno analysis show significant increase in power output compared to conventional products
- Improved fuel economy and lower oil consumption
- Advanced surface chemistry optimises anti-wear performance giving vital protection to pistons, bores, cams and bearings even under race conditions
- Enhanced high temperature deposit control resulting in a cleaner engine and promoting longer engine life
- Outstanding gear wear and pitting protection
- Balanced frictional properties give precise clutch control / operation
- Also provides good corrosion protection, oxidation / nitration resistance, lower volatility

XP
TECHNOLOGY

11% FUEL SAVINGS | **18% LOWER OIL CONSUMPTION** | **3% INCREASED POWER**

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44 (0)1782 203700
contact-uk@fuchs.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Product Information



Typical Data: SILKOLENE PRO 4 XP RANGE

SILKOLENE PRO 4 ..	Test Method	Unit	10W-30 XP	10W-40 XP	10W-50 XP	10W-60 XP
Appearance			Red	Red	Red	Red
SAE Rating			10W-30	10W-40	10W-50	10W-60
Specific Gravity at 15°C	IP160		0.860	0.861	0.861	0.862
Kinematic Viscosity @ 40°C	IP71	mm ² /s	72.68	103.9	122.9	167.8
Kinematic Viscosity @ 100°C	IP71	mm ² /s	11.61	15.8	18.7	24.4
Viscosity Index (VI)	IP226		154	162	171	178
Cold Crank Viscosity 10W @ -25°C	ASTM D5293	cP	4700	5455	4597	6197
Flash point	IP34	°C	204	214	212	206
Pour point	IP15	°C	-39	-36	-33	-30

SILKOLENE PRO 4 ..	Test Method	Unit	5W-40 XP	15W-50 XP
Appearance			Red	Red
SAE Rating			5W-40	15W-50
Specific Gravity at 15°C	IP160		0.858	0.866
Kinematic Viscosity @ 40°C	IP71	mm ² /s	92.8	134.8
Kinematic Viscosity @ 100°C	IP71	mm ² /s	15.8	18.8
Viscosity Index (VI)	IP226		179	158
Cold Crank Viscosity 5W @ -30°C	ASTM D5293	cP	5809	
15W @ -20°C		cP		4880
Flash point	IP34	°C	210	208
Pour point	IP15	°C	-36	-30

Updated Nov 2019 ABUK



11% FUEL SAVINGS | **18% LOWER OIL CONSUMPTION** | **3% INCREASED POWER**

FUCHS LUBRICANTS (UK) plc
New Century Street, Hanley

Tel: +44 (0)1782 203700

